

MERAS ENGINEERING INC 2401 E ORANGEBURG AVE MODESTO, CA 95355

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product Identifier: MICRO SAN 150

Product Code: 33

Registration Number: 63838-2

MERAS ENGINEERING INC
 2401 E ORANGEBURG AVE #675
 MODESTO, CA 95355
 (415)240-4918

24 Hr. Emergency Tel.#: 800-262-8200

SECTION 2 - HAZARDS IDENTIFICATION

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA). These requirements differ from the classification criteria and hazard information required for safety data sheets of non-pesticide chemicals. Please see Section 15 for FIFRA labeling information.

Classification of the Substance or Mixture:

Skin Corrosion - Category 1
 Serious Eye Damage - Category 1
 Oxidizing Liquids - Category 2
 Corrosive to Metals - Category 1
 Organic Peroxides - Type F
 Acute Toxicity - Oral Category 4
 Acute Toxicity - Dermal Category 5
 Hazardous to the Aquatic Environment, Acute Toxicity Category 2


Signal Word: DANGER

Hazard Statements:

Causes severe skin burns and eye damage
 May intensify fire; oxidizer
 May be corrosive to metals
 Harmful if swallowed
 May be harmful in contact with skin
 Toxic to aquatic life
 Heating may cause fire

Precautionary Statements:

Wear protective gloves/protective clothing/eye protection/face protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 Keep away from heat/sparks/open flames/hot surfaces - No smoking.
 Keep/Store away from clothing/.../combustible materials.
 Take any precaution to avoid mixing with combustibles.
 Keep only in original container.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Concentration
HYDROGEN PEROXIDE	7722-84-1	21.5-22.5%
PEROXYACETIC ACID	79-21-0	14.8-15.7%
ACETIC ACID	64-19-7	15.8-16.6%

SECTION 4 - FIRST-AID MEASURES

Inhalation: Remove source of exposure or move person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. Symptoms of pulmonary edema can be delayed up to 48 hours after exposure. If direct contact during rescue breathing poses a threat to the first aid provider, "Avoid mouth-to-mouth contact by using a barrier device."

MERAS ENGINEERING INC 2401 E ORANGEBURG AVE MODESTO, CA 95355

SAFETY DATA SHEET

Skin Contact: Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Rinse skin with lukewarm, gently flowing water/shower with a flushing duration of 30 minutes. Immediately call POISON CENTER/doctor. Wash contaminated clothing before re-use.

Eye Contact: Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 30 minutes. Take care not to rinse contaminated water into the unaffected eye or into the face. Immediately call a POISON CENTER/doctor.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

Most Important Symptoms and Effects, both Acute and Delayed: Causes severe skin burns and eye damage, burning of the mouth, throat, and esophagus.

Indication of any Immediate Medical Attention and Special Treatment Needed: Treat symptomatically

SECTION 5 - FIRE-FIGHTING MEASURES

Extinguishing Media: Use water spray, powder, foam, carbon dioxide.

Special hazards arising from the substance or mixture: Non combustible. May give off irritating or toxic fumes (or gases) in a fire.

Flammability classification (OSHA 29 CFR 1910.106) (Hazcom 2012): Non flammable

Hazardous Combustion Products: May cause fire and explosions when in contact with incompatible materials.

Special protective equipment and precautions for firefighters: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

Methods and materials for containment and cleaning up: SMALL SPILLS (less than 1 gallon): Neutralize with soda ash or cover with dry earth, sand or other non combustible material, place into loosely covered plastic containers for later disposal. If neutralized, material can be diluted into drain. LARGE SPILL: Restrict access to area until completion of clean up. Prevent liquid from entering sewers or waterways. Stop or reduce leak if safe to do so. Dike with inert material (sand, earth, etc.). Collect into plastic containers for disposal. Ensure adequate decontamination of tools and equipment following clean up.

Special spill response procedures: Collect spills in plastic containers only. Prevent from entering sewers, waterways, or low areas.

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling: Wear at least chemical resistant gloves and eye protection, face shield, and chemical resistant garments when handling, moving or using this product. Do not contaminate water, food, or feed by storage or disposal.

Conditions for Safe Storage: Store in a cool, dry, well ventilated place away from direct sunlight. Keep container closed when not in use.

Incompatible Materials: Avoid strong reducing agents, soft metals, heat and bases (unless product has been diluted to less than 1000ppm, then bases may be used to gradually adjust to a pH of less than 9).

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS:		OSHA PEL		ACGIH TLV	
		TWA	STEL/CEILING	TWA	STEL
CHEMICAL NAME	CAS NO.				
ACETIC ACID	64-19-7	10 ppm	15 ppm/40 ppm (CalOSHA)	10 ppm	15 ppm
HYDROGEN PEROXIDE	7722-84-1	1 ppm	1 ppm/N/A (CalOSHA)	1 ppm	N/A
PERACETIC ACID	79-21-1	N/A	N/A	N/A	0.4 ppm

Ventilation and engineering measures: Forced air, local exhaust, or open air is adequate.

Respiratory Protection: In case of confined spaces or high levels encountered in the air, wear self contained breathing apparatus.

Skin Protection: Wear chemical resistant gloves and chemical resistant garments when handling, wash garments before re-use.

Eye/Face Protection: Wear chemical goggles; also wear a face shield if splashing hazard exists.

Other Protective Equipment: Eye wash facility and emergency shower should be in close proximity.

General Hygiene Conditions: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industry hygiene and safety practice.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear colorless liquid

Odor: Vinegar odor

pH: <1 (1:10)

Melting/Freezing point: <10° F / <-12 ° C

Initial boiling point and boiling range: No information available

SAFETY DATA SHEET

Flash Point: >207° F / >98 ° C
Flammability (solid, gas): Non flammable
Vapor Pressure (mm Hg): 27
Specific gravity: 1.14 g/mL
Solubility in Water: Complete
Auto ignition Temperature: >518° F/ >270° C
Decomposition temperature: No information available
Viscosity: 10-20 cSt at 20°C / 68°F
Volatiles (% by weight): >99
Volatile Organic Compounds (VOC's): No information available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: Reactive with bases, metals, reducing agents and combustible materials
Chemical Stability: Stable for up to 1 year when stored under normal conditions.
Possibility of Hazardous Reactions: May react with incompatible materials
Conditions to Avoid: Incompatible materials and high temperatures
Incompatible Materials: Reactive with bases, metals, reducing agents and combustible materials
Hazardous Decomposition Products: Oxygen which supports combustion.

SECTION 11 - TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry - inhalation: YES
Routes of entry - skin & eye: YES
Routes of entry - ingestion: YES
Routes of entry - skin absorption: NO

Potential Health Effects:

Signs and symptoms of short term (acute) exposure:

Inhalation: Inhalation of the mist may produce severe irritation of respiratory tract, characterized by coughing, choking, shortness of breath, headaches, dizziness, nausea, weakness and/or drowsiness.

Ingestion: Corrosive! Swallowing causes severe burns of mouth, throat, and stomach. Severe scarring of tissue, corrosion, permanent tissue destruction and death may result. Symptoms may include severe pain, nausea, vomiting, diarrhea, shock, hemorrhaging and/or fall in blood pressure. Damage may appear days after exposure.

Skin: Corrosive! Contact with skin causes irritation or severe burns and scarring with greater exposures.

Eye: Corrosive! Causes irritation of eyes, and with greater exposures it can cause burns that may result in permanent impairment of vision, even blindness.

Potential Chronic Health Effects:

Mutagenicity: Not known to have mutagenic effects in humans or animals.

Carcinogenicity: Not expected to be a carcinogen or tumorigen.

Reproductive effects: No known reproductive effects in humans or animals.

Sensitization to material: Not a known sensitizer in humans or animals.

Specific target organ effects: No information available.

Medical conditions aggravated by overexposure: No information available

Toxicological data: The calculated ATE values for this mixture are:

ATE oral = 494 mg/kg

ATE dermal = 2281 mg/kg

ATE inhalation = >20 mg/L or >20,000 ppm

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: May harmful to aquatic life.

Persistence and degradability: Not expected to persist. Expected to readily biodegrade.

Bioaccumulation potential: Not expected to bio accumulate.

MERAS ENGINEERING INC 2401 E ORANGEBURG AVE MODESTO, CA 95355

SAFETY DATA SHEET

Mobility in soil: No information available

SECTION 13 - DISPOSAL CONSIDERATIONS

Handling for disposal: Do not contaminate water, food, or feed by storage and/or disposal. When handling refer to protective measures listed in sections 7 and 8. Empty residue from containers, rinse container well.

Method of disposal: Dispose of in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

RCRA: If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of: Corrosivity D002

SECTION 14 - TRANSPORTATION INFORMATION

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

Please note the GHS and DOT Standards are NOT identical and therefore can have varying classifications

US 49 CFR/DOT/IATA/IMDG Information:

UN No.: 3109

UN Proper Shipping Name: Organic peroxide type F, liquid (peroxyacetic acid)

Transportation hazard class(es): 5.2 (8)

Packing Group: II

Environmental hazards: Not a Marine Pollutant

SECTION 15 - REGULATORY INFORMATION

FIFRA Classification/Typical Hazard Labeling, as outlined in EPA Label Review Manual

Hazard Data

Signal Word	DANGER
Acute Toxicity, oral	Category III: Harmful if swallowed
Acute Toxicity, dermal	Category III: Harmful if absorbed through skin
Acute Toxicity, inhalation	Category IV
Skin irritation/corrosion	Category I: Corrosive. Causes skin burns
Serious eye damage	Category I: Corrosive, Causes irreversible eye damage
Sensitization	Not Classified (NC)
Environmental (aquatic) toxicity	This pesticide is toxic to fish and other aquatic organisms.

US Federal Information:

TSCA information: All components are listed on the TSCA inventory.

US CERCLA Reportable quantity (Hazardous substance RQ): Acetic acid has a RQ of approximately 31000 lbs. of as is chemical.

US EPCRA Reportable quantity (Extremely hazardous substance RQ): Peracetic acid has a RQ of approximately 3500 lbs. of as is chemical.

SARA Title III: Reactivity Hazard, Acute Health Hazard

International Information: WHMIS: Class C: Oxidizing material. Class E: Corrosive material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations.

SECTION 16 - OTHER INFORMATION

Legend:

SARA: The Superfund Amendments and Reauthorization Act

RCRA: Resource Conservation and Recovery Act

TSCA: Toxic Substances Control Act

CFR: Code of Federal Regulations

DOT: Department of Transportation

ATE: Acute Toxicity Estimate

Preparation date: 9/23/2015